

Listing and Amendments to the Claims

This listing of claims will replace the claims that were published in the PCT Application:

[001] (Currently amended) ~~Method~~ A method of enciphering/deciphering a message to be exchanged between a sender and a receiver by way of a communication network, the sender and the receiver both being one among a secure device (1) and a defined client device (C_i) in a network of client devices (C_i, C_j), the method comprising the steps of:

- performing operations of asymmetric cryptography by the secure device (1) and by the defined client device (C_i) respectively with the aid of a private key (n_i, d_i) and of a public key (n_i, e_i), the private key being different from the public key, and

- dispatching (62, 81) at least one public data item (n_i, CID_i) from the defined client device (C_i) to the secure device (1),

~~characterized in that it~~ Wherein the method comprises furthermore, during each send/receive of a message enciphered by the secure device, a step of determining the private key (n_i, d_i) corresponding to the public key (n_i, e_i) of the defined client device (C_i), on the basis of a secret master key (MK) stored in the secure device, and the or each public data item (n_i, CID_i) dispatched by the defined client device (C_i).

[002] (Currently amended) ~~Method~~ The method of enciphering/deciphering a message according to Claim 1, ~~characterized in that~~ wherein the step of dispatching (62, 81) the or each public data item comprises a step of dispatching a part (n_i) of the public key, this part of the public key forming a first part of the private key.

[003] (Currently amended) ~~Method~~ The method of enciphering/deciphering a message according to ~~any one of Claims 1 and 2~~ claim 1, characterized in that ~~wherein~~ the step of dispatching ~~(62, 81)~~ the or each public data item comprises a step of dispatching an identifier $\{CID_i\}$ of the client device $\{C_i\}$, and the step of determining the private key comprises a step of calculating a second part $\{d_i\}$ of the private key on the basis of the said dispatched identifier.

[004] (Currently amended) ~~Method~~ The method of enciphering/deciphering a message according to Claim 3, characterized in that ~~wherein~~ the step of determining the private key $\{n_i, d_i\}$ corresponding to the public key $\{n_i, e_i\}$ of the client device, comprises a step of enciphering ~~(44, 64, 83)~~ the result $\{ECID_i\}$ of a function applied to the identifier $\{CID_i\}$ of the defined client device $\{C_i\}$, by a symmetric algorithm, with the aid of the secret master key $\{MK\}$.

[005] (Currently amended) ~~Method~~ The method of enciphering/deciphering a message according to Claim 4, characterized in that ~~wherein~~ the step of determining the private key $\{n_i, d_i\}$ corresponding to the public key $\{n_i, e_i\}$ of the client device, comprises a step of selecting ~~(45, 65, 84)~~ the second part $\{d_i\}$ of the private key, by a deterministic calculation unit ~~(8)~~, on the basis of the result of the said enciphering of the result $\{ECID_i\}$ of a function applied to the identifier $\{CID_i\}$ of the defined client device $\{C_i\}$.

[006] (Currently amended) ~~Method~~ The method of enciphering/deciphering a message according to Claim 5, characterized in that ~~wherein~~ the step of selecting the second part $\{d_i\}$ of the private key, by the deterministic algorithm, is performed by a selection of a number such that:

- this number is less than the result of the said encipherment of the result $\{ECID_i\}$ of a function applied to the identifier $\{CID_i\}$ of the defined client device $\{C_i\}$,
- this number is the closest to the result of the said encipherment of the result $\{ECID_i\}$ of a function applied to the identifier $\{CID_i\}$ of the defined client device $\{C_i\}$, and is prime to a list of prime numbers.

[007] (Currently amended) ~~Method~~ The method of enciphering/deciphering a message according to ~~any one of Claims 3 to 6~~ claim 3, characterized in that wherein it comprises a step of destruction ~~(49, 67, 87)~~ of the identifier $\{CID_i\}$ of the defined client device $\{C_i\}$ and of all the data $\{p_i, q_i, d_i, ECID_i, e_i, n_i\}$ calculated on the basis of the identifier so as to determine the private key.

[008] (Currently amended) ~~Method~~ The method of enciphering/deciphering a message according to ~~any one of the preceding claims~~, characterized in that claim 1 wherein the cryptography operations comprise an operation for identifying a message comprising the following steps:

- signature of the message $\{85\}$, by the secure device $\{1\}$, with the aid of the private key $\{n_i, d_i\}$ determined during the step of determining the private key,
- transmission of the signature of the message and of the message $\{86\}$ to the client device for verification of this signature, and
- verification of the signature $\{87\}$ of the message, by the client device, with the aid of the said public key $\{n_i, e_i\}$.

[009] (Currently amended) ~~Method~~ The method of enciphering/deciphering a message according to ~~any one of the preceding claims~~ claim 1, characterized in that wherein the cryptography operations comprise an operation for securing a message comprising the following steps:

- encipherment (61) of a message (m), by the client device (C_i), with the aid of the public key (n_i, e_i),
- transmission (62) of the enciphered message to the secure device (1), and
- decipherment (66) of the message enciphered by the secure device (1), with the aid of the private key (n_i, d_i) determined during the step of determining a private key.

[010] (Currently amended) Method ~~The method~~ of enciphering/deciphering a message according to ~~any one of Claims 3 to 9~~ claim 3, characterized in that wherein it comprises a prior phase of personalizing the said defined client device (C_i), which comprises the following steps:

- generation, by the secure device (1), of a unique secret master key (MK) and of an identifier (CID_i) specific to the said defined client device (C_i) and able to identify it,
- calculation of the said public key (n_i, e_i) of the defined client device (C_i) by a calculation module (5) on the basis of the second part (d_i) of the private key.

[011] (Currently amended) Method ~~The method~~ of enciphering/deciphering a message according to Claim 10, in which the personalization phase furthermore comprises the following steps:

- selection (46) of two secret data consisting of two large prime numbers p_i , q_i , such that $(p_i-1) \times (q_i-1)$ is prime to the second part (d_i) of the private key of the defined client device (C_i), and
- calculation (48) of a modulus n_i of the defined client device (C_i) such that:
$$n_i = p_i \times q_i, \text{ and}$$
- calculation (48) of a part (e_i) of the public key by an extended Euclid algorithm on the basis of the or of each secret data item p_i , q_i and of the modulus n_i of the defined client device (C_i).

[012] (Currently amended) ~~Secure~~ A secure device (1) able to exchange a message with a defined client device (C_i) of a network of client devices (C_i, C_j), over a communication network, the secure device being able to receive at least one public data item (CID_i, n_i) specific to the said defined client device (C_i) and dispatched by the latter prior to any exchange of messages, the secure device (1) comprising:

- means for performing operations of asymmetric cryptography with the aid of a private key (n_i, d_i) corresponding to a public key (n_i, e_i) stored in the defined client device (C_i)

~~characterized in that~~ wherein it comprises, furthermore:

- secure means of storage (3) of a master key (MK),
- means (4) of determination of the said private key (d_i, n_i) on the basis of the master key (MK) and of the or of each public data item (CID_i, n_i) dispatched.

[013] (Currently amended) ~~Secure~~ The secure device according to Claim 12, ~~characterized in that~~ wherein the public data item (CID_i, n_i) comprises a part (n_i) of the public key of the said defined client device (C_i) and/or an identifier (CID_i) of the defined client device.

[014] (Currently amended) ~~Secure~~ The secure device according to Claim 13, ~~characterized in that~~ wherein the private key is a mixed key comprising a first part (n_i) corresponding to a part of the public key (n_i, e_i) of the said defined client device (C_i) and a second secret part (d_i) calculated on the basis of the master key (MK) and of the identifier (CID_i) of the defined client device.

[015] (Currently amended) ~~Secure~~ The secure device according to ~~any one of Claims 12 to 14~~ claim 12, ~~characterized in that~~ wherein the means for performing operations of asymmetric cryptography with the aid of the private key (d_i, n_i) determined comprise:

- means of signature (S) of a message (m), and
- means of encipherment (E) of a message (m).

[016] (Currently amended) ~~Secure~~ The secure device according to ~~any one of Claims 14 to 15~~ claim 14, in which the means of determination (4) of the private key comprise furthermore:

- a unit for symmetric encipherment (7), with the aid of the master key (MK), able to encipher the result ($ECID_i$) of a function applied to the identifier (CID_i) of the defined client device (C_i), and/or
- a unit for calculation (8) of a deterministic algorithm for selecting the second secret part (d_i) of the private key on the basis of the result of the encipherment produced by the unit (7) for symmetric encipherment.

[017] (Currently amended) ~~Secure~~ The secure device according to ~~any one of Claims 14 to 16~~ claim 14, characterized in that ~~wherein~~ it furthermore comprises a means of initialization of the client devices of the network, the said means of initialization comprising:

- a means of random generation (2) of a unique master key (MK) and of a plurality of mutually distinct identifiers (CID_i, CID_j), each identifier being apt to characterize a unique client device (C_i) of the client device network,
- a unit for calculation (9) able to select two secret data items (p_i, q_i) as a function of the value of the second secret part (d_i) of the private key and to calculate a first part (n_i) of the public key, and
- a unit for calculation (10) of the second part (e_i) of the public key, by an Extended Euclid algorithm, on the basis of the secret data (p_i, q_i), of the second part (d_i) of the private key and of the first part (n_i) of the public key.

[018] (Currently amended) ~~Computer~~ A division program comprising instructions for the execution of the method steps for enciphering/deciphering a message according to ~~any one of Claims 1 to 11~~ claim 1, when the program

Customer No.: 24498

is executed on a secure device embodied on the basis of a programmable calculator.

[019] (Currently amended) ~~Recording—~~ A recording medium usable on a secure device embodied on the basis of a programmable calculator on which is recorded the program according to Claim 18.